



ELISA
copyright display for patisserie



ELISA S

Elisa S is an elegant refrigerated cabinet for upright displaying of patisserie products. The model has rear sliding glass doors and its stainless steel lower display deck is a drawer system, which is convenient to slide out for product placement. Wide lower display surface and 3-level glass shelves provide optimal product visibility. Stylish curved shape Elisa S is a great choice for the appetizing display of cakes, pies, pastries and other desserts. Suitable for any format retail stores, bakery shops and canteens. Can be multiplexed.

OPTIONS:

- | Stainless steel or powder coated display surface

KEY BENEFITS:

- | Round glass structure
- | External colour – any RAL or imitation of wood
- | Multiplexable device
- | Panoramic endwalls
- | 3 levels of glass shelves
- | Retractable shelf
- | 4 levels of LED shelf lighting
- | Sliding doors of insulated glass
- | Control panel
- | Thermometer (solar powered or electronic)
- | Energy-saving fans
- | Polyurethane thermal insulation CFC free

mm	940	1250	1880	2500	3750
°C	N/A				



	R134A	R448A	R450A	CO ₂	R290
PLUG-IN	✓	✓			✓
REMOTE	✓	✓	✓	✓	
HYDROLOOP	✓	✓			✓



ELISA QB

Elisa QB is an attractive refrigerated bakery and pastry display cabinet. Straight glass design, elegant glass shelves allow to show products at their best and increase impulse purchases. Stylish and practical, Elisa QB is perfect to appetizingly display sweets while preserving their freshness. It features wide space for product presentation, 4 exhibition levels, panoramic glass view, rear sliding glass doors and lower display deck with a drawer system for easy access to products. Great choice for supermarkets, shopping malls, bakery shops and catering industry.

OPTIONS:

| Stainless steel or powder coated display surface

KEY BENEFITS:


- | External colour – any RAL or imitation of wood
- | Multiplexable device
- | Panoramic endwalls
- | 3 levels of glass shelves
- | Retractable shelf
- | 4 levels of LED shelf lighting
- | Sliding doors of insulated glass
- | Control panel
- | Thermometer (solar powered or electronic)
- | Energy-saving fans
- | Polyurethane thermal insulation CFC free

MM	940	1250	1880	2500	3750
°C	N/A				




	R134A	R448A	R450A	CO ₂	R290
PLUG-IN	✓	✓			✓
REMOTE	✓	✓	✓	✓	
HYDROLOOP	✓	✓			✓

Model	Length without endwalls (mm)	Operating temperature °C (+25 °C, 60% RH)	Exposition space (m ²)	Volume (m ³)	Rated voltage (V)
Elisa S	940	1...10 °C H1	1.55	0.42	230
	1250		2.06	0.56	
	1880		3.01	0.85	
	2500		4.13	1.13	
	3750		6.19	1.69	
Elisa QB	940	1...10 °C H1	1.55	0.42	230
	1250		2.06	0.56	
	1880		3.01	0.85	
	2500		4.13	1.13	
	3750		6.19	1.69	



Elisa S



Elisa QB



ELISA S - REAR SIDE